


BCT36 Blast Chiller Cabinet BCT36



Temperature







Capacity

36 Chilling (Kg)

Unpacked Weight

Features & Benefits

The Foster tray loading blast chiller range provides the ideal way to ensure quality and food safety is maximised in every kitchen, large or small

- High Quality 304 Stainless Steel Exterior Build Quality
- Capable of blast chilling from +7°C to +3°C in 90 minutes
- Intuitive easy touch control panel Just press and go with easy to use colour coding to indicate cycle status.
- HACCP software is available as an option in 3 formats for data retrieval and management
- Bottom mounted refrigeration system ensures stability and helps performance

External Finish		Doors		Electrical Data & Service	
304 Stainless Steel 304 Stainless Steel Rear	Standard Option	Solid Full Hinged - Right Hand	Standard Standard	Information 230 Volts	Standard
For Island Siting		Hinged - Left Hand	Option	50Hz	Standard
Internal Finish		Refrigeration		60Hz	Option
				1 Phase	Standard
304 Stainless Steel	Standard	Integral	Standard	Running Watts	1808
Shelving		R404a	Standard	Running Amps	6.5
Additional	Option	Drain Required?	No	Thermal Heat Rejection (W)	2,018
Shelf				Noise (dBa @ 1m)	67.5
Stainless Steel	Option			Fuse Required (A)	16 amp
Gastronorm				Product Extras	
1/1 Shelf Nylon	Option			Door Pull Handle	Standard
Coated	Option			Hold Facility	Standard
Gastronorm				Temperature Probe	Standard
1/1 Shelf				Hardwired Logging System	Option
Base Fittings				Interface	
80mm Castors	Standard				
Legs	Option				

Footnotes

• Chilling Capacity - 36 KG. Chilling capacity 70oC to 3oC in less than 90 minutes within specifications, entry temperature up to 90oC for chilling.

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com











ISO 14001



Demand more. Choose Foster