

Ice and water dispenser up to 209 kg



Shown with optional KLP24A legs



Features

Smarter Construction - Durable stainless steel evaporator and exterior panels. Greaseless bearings for reduced maintenance. Larger sink opening and dispensing area. Antimicrobial AquaArmor with AgION is molded into key components.

Space maximizing design - The industry's smallest operational footprint relative to capacity. Featuring specially designed contoured sides for enhanced breathability and an external air filter.

More convenient front access - Removable front panels allow ease of access and service to all key internal components. Including removable storage bin for better cleaning and maintenance access.






Enhanced service features - Intuitive LED diagnostic lights reduce service time. Unit specific QR code for quick access to service manuals and warranty history. Convenient USB drive that allows for fast software updates. New removable sink and grill provide maximum access for ease of cleaning.

Energy and Water Efficiency - Industry leading efficiencies deliver on going savings.

Quieter operation - Improved condenser fan function.

Technologies



				
	+C° -C°	21°C : 10°C [kg] [lb]	32°C : 21°C [kg] [lb]	[kg] [lb]
HID 525 AS		209 460	152 335	11 25

 [V/Hz/ph] 220-240/50/1	 R404A	 D W H [WxDxH mm] 542 x 619 x 886 [WxDxH inches] 21,36" x 24,38" x 34,88"
--	--	--

This product qualifies for the following listings:



Certified ISO 9001:2008



Chewable, slow-melting ice that allows for more reliable dispensing.

19 mm x 8 mm x 9,5 mm
(3/4" x 5/16" x 3/8")

2 Years Warranty


Subject to certain limitations and exclusions



Apple store
Google play
Windows store

www.scotsman-ice.it
www.scotsman-ice.com

Ice and water dispenser up to 209 kg



All models include 7.5' power cord with NEMA 5-15P plug

Installation Note: Allow 6" space at left, back and right side for ventilation and utility connections.

Minimum		Maximum
10°C (50°F)		38°C (100°F)
5°C (40°F)		38°C (95°F)
-10%		+10%
1,4 bar 20 psi		5,5 bar 80 psi

	+C° -C°	[Btu/h] [W]	[Ømm ²]	[W]	FUSE	[kWh] - 100 kg	[l/h]	[gal/h]	[kg] [lb]
HID 525 AS		6800 1992	3x1,5	800	15 A	12,6	6,4	1,7	95 208

IMPORTANT NOTICE:
 Models and specifications are subject to change without notice.
 This spec sheet is meant for commercial purpose only.
 For technical documentation please refer to our service manuals.

www.scotsman-ice.it
www.scotsman-ice.com