

BARS - TAKEAWAY OUTLETS - RESTAURANTS - HOTELS - CANTEENS





J 100 Ultra AUTOMATIC JUICER

2 WAYS OF USING YOUR JUICER

Continuous pulp ejection

Ejection chute sending continuous flow of pulp directly into bin under worktop.





Pulp ejected into container

7.2-litre large-capacity translucent pulp container
















UNIQUE INNOVATION

AUTOMATIC JUICERS

J 80 Ultra • J 100 Ultra



Patented automatic feed tube with a diameter of 79 mm for continuous throughput and hassle-free juicing.







: 450 587 - 12/2010 - Anglais

AUTOMATIC JUICERS

J 80 Ultra • J 100 Ultra



Product benefits:

- Automatic: the unique design of the feed tube does away with the need for a pusher! You can now produce high volumes of top-quality juice quickly and effortlessly!
- High power, low noise levels: the powerful, heavy-duty motor operates at a speed
 of 3,000 rpm, meaning that the juice oxidizes less quickly. The resulting juices are
 particularly smooth and bursting with flavour. The noise levels of the J 80 Ultra/
 J 100 Ultra are so low that they can be used right in front of the customer.
- **Practical:** the drip tray can hold up to 300 ml of liquid, meaning that your worktop stays clean.
- Large-capacity pulp container! the 6.5-litre (J 80 Ultra) or the 7.2-litre (J 100 Ultra) translucent container slots neatly underthe ejector spout, to avoid pulp splashing onto the worktop.

The J 100 Ultra can be used in two ways:

- 1. Continuous pulp ejection: ejection chute sending a continuous flow of pulp directly into a bin beneath the worktop.
- 2. Pulp ejected into a container: 7.2-litre large-capacity translucent pulp container.
- Centrifugal juicer basket: the basket can be removed (no special tool required) for easy cleaning.



Users:

Bars, takeaway outlets, restaurants, hotels, canteens



In short:

They have all the qualities you could ask for in a juicer: fast, resilient, efficient, and top-quality juice.



Video available on: www.robot-coupe.com



INDUCTION MOTOR


- Heavy-duty motor designed to withstand intensive use for greater reliability and a longer lifespan.
- Ball bearing-supported motor for ultra-quiet, vibration-free operation.
- Direct-drive motor:
 - extra power
 - no belt
- Maintenance-free: no wearing parts (no brushes)
- Stainless-steel motor shaft





	Electrical characteristics			Dimensions (mm)				Weight (kg)	
	Speed (rpm)	Power (W)	Voltage* (A)	А	В	С	D	Net	Gross
J 80 Ultra	3000	700	230 V/ 50 Hz/ 1	505	535	235	162	10.9	12.8
100 Ultra	3000	1000	230 V/ 50 Hz/ 1	596	538	235	256	12.9	15.6

^{*} Other voltages available





HEAD OFFICE, FRENCH, EXPORT AND MARKETING DEPARTMENT:

Tel.: + 33 1 43 98 88 33 - Fax: + 33 1 43 74 36 26 email: international@robot-coupe.com

Robot Coupe Australia: Tel.: (02) 9478 0300 - Fax: (02) 9460 7972 New Zealand: Tel.: 0800 716161 - Fax: 0800 716162 email: orders@robotcoupe.com.au

Robot Coupe U.K. LTD: Tel.: 020 8232 1800 - Fax: 020 8568 4966 2, Fleming Way, Isleworth, Middlesex TW7 6EU email: sales@robotcoupe.co.uk

Robot Coupe U.S.A.: Tel.: 1-800-824-1646 - Fax: 601-898-9134 email: info@robotcoupeusa.com - website: www.robotcoupeusa.com

www.robot-coupe.com

DISTRIBUTOR

STANDARDS:

Machines in compliance with:

- The essential requirements of the following European directives and with the corresponding national regulations: 2006/42/EC, 2006/95/EC, 2004/108/EC, 1935/2004/EC, 2002/72/EC, "RoHS" 2002/95/EC, "WEEE" 2002/96/EC.
- the requirements of the European harmonized standards and with the standards specifying the hygiene and safety requirements: EN 12100-1 and 2 2004, EN 60204-1 2006, EN 1678 1998, EN 60529-2000: IP 55, IP 34.

