RACK OVENS

C-SERIES – RACK OVEN

The C-Series is a flexible and user-friendly series of compact rack ovens developed to be highly efficient and designed to fit into small spaces. The C-Series is also available in an eco+ design, providing extra high energy efficiency and savings.

FEATURES AND BENEFITS

Heating package integrated into the top section. Requires little floor space.

Equipped with our Increased Baking Surface system (IBS). Allows for quick, even and economical baking.

Comes with a SD-Touch panel.

Simple, logical, programmable and effective control of the oven.

Retains the heat inside the oven.

Strong, stainless steel interior and exterior.

Robust materials which extend the oven's life. Easy to clean.

Large, efficient heating package – flexible production.

Quick heating and efficient use of heat.

Integrated high capacity steam system. Gives a smooth, crisp crust and for some breads a significantly increased volume.

Efficient heat exchange in oil and gas ovens.

High efficiency, low heating cost.

Spring loaded hinge.

Ensures doors remain opened when loading and unloading racks.

Automaic rotation stop.

When door handle is realeased (not opening the door) The rack will rotate to undloading position.

Right hand hinged door with double glazed window. Easy to open and gives a good view of the oven interior.

Suspension hook is standard. Max weight 150 kg on C100, 200 kg on C200 Simplifies oven cleaning.

Frequency-controlled fans which direct the airflow (optional). Adjustable airflow of heat and steam when baking sensitive products such as meringues and macaroons.

Max baking temperature 330°C.

OPTIONS

Rotating platform with adjustable ramp

Heavy duty platform

Automatic rack lifting device

Large window in door

Insulated floor (standard eco+)

Left hand hinged door

AES - Automatic Evacuation System

Fully assembled oven

Slow start

Canopy

Canopy with exhaust fan

Spring loaded door hinge

Variable speed for fans

Automatic rotation stop



TECHNICAL

MODEL	C100MA	C200MA
HEATING POWER	30-35-40 kW	40-45-50 kW
MAX TRAY SIZE	457 x 762 mm	600 x 800 mm
MAX DIAGONAL RACK	935 mm	1050 mm
MAX RACK HEIGHT: – PLATFORM	1585 mm	1585 mm
- HOOK	1640 mm	1640 mm

MEASUREMENTS, EXTERNAL

